





C4040 LEB

# Leonardo Braccio



I Rinnovato modello completamente in acciaio e alluminio verniciati a polveri epossidiche grigio antracite. Ombrellone particolarmente robusto e adatto per uso professionale.

UK Renewed model completely in steel and aluminium epoxy lacquered. Particularly strong parasol suitable for a professional employ.

D Erneueres Model ganz aus pulverbeschichtetem Stahl und Aluminium. Besonders starker Schirm geeignet fuer einen gewerblichen Einsatz.

F Modèle complètement retravaillé en acier et aluminium avec vernis époxy. Parasol particulièrement robuste et adapté pour une utilisation professionnelle.

E Modelo completamente renovado en acero y aluminio lacado. Sombrilla particularmente fuerte, apropiada para usos profesionales.

NL Vernieuwd model, geheel gefabriceerd uit geëpoxeerd staal en aluminium. Een ideale parasol voor intensief gebruik (waaronder de horeca).



## 16. Leonardo Braccio

I

Ombrellone a braccio laterale robusto. Telaio: Alluminio e componenti in acciaio; verniciato a polveri colore antracite. Accessori in nylon.

F

Parasol bras deporté robuste. Armature: Aluminium vernis couleur gris anthracite. Accessoires en nylon.

UK

Strong cantilever parasol. Frame: Powder coated aluminium anthracite grey. Nylon accessories.

E

Brazo lateral resistente. Estructura: aluminio y piezas de acero, recubierto con polvo de antracita. Accesorios de nylon.

D

Starker Pendelschirm. Gestell aus pulverbeschichtetem Aluminium Farbe Anthrazitgrau. Zubehoer aus Nylon.

NL

Robuuste vrijhangende parasol. Mast en baleinen: grijs geëpoxeerd aluminium en staal.

↑ ↔	COD	MEASURES		CHARACTERISTICS						
		KG	M <sup>3</sup>	92x92	ALU DARK	8	ALU DARK	18x30		
	4,0 C4000 LEB			68	0,35	92x92	ALU DARK	8	ALU DARK	18x30
	3,0x3,0 C3030 LEB			68	0,35	92x92	ALU DARK	8	ALU DARK	18x30
	3,5x3,5 C3535 LEB			70	0,36	92x92	ALU DARK	8	ALU DARK	18x30
	4,0x4,0 C4040 LEB			100	0,48	92x92	ALU DARK	8	ALU DARK	18x35
	3,0x4,0 C3040 LEB			70	0,36	92x92	ALU DARK	8	ALU DARK	18x30



**SCOLARO Mario & Fabio srl**

Via Liguria, 197 - 35040 Casale di Scodosia (PD)  
 ITALY - TEL. +39 0429 656687 - FAX. +39 0429 657874  
 info@scolaro-parasol.it - www.scolaro-parasol.it

FINISHING									COLOUR RANGE							OPTIONAL		BASES				
									ACRYL 350 GR									N°2 BC5151 N°6 BC5050	N°4 BC5151 N°12 BC5050	N°2 BV5050	N°4 BV5050	FISSAGGIO TERRA INGROUND FIX
									A1	A1	A2	A3	A6	A7	S1							
•	•	•	•	•	•	•	•	•	-		-	-	-	-	-	•	•	/		/		
•	•	•	•	•	•	•	•	•								•	•				/	
•	•	•	•	•	•	•	•	•								•	•				/	
•	•	•	•	•	•	•	•	•								•	•	/		/		
•	•	•	•	•	•	•	•	•								•	•				/	

#### Ombrellone a braccio robusto in alluminio.

**TELAIO:** Interamente in alluminio e acciaio verniciati a polveri colore grigio antracite. Sostegno verticale sez. 92x92 mm.

Stecche in alluminio sezione 18x30 mm (18x35mm per misura 4x4), facilmente intercambiabili abbinata al nuovo sistema di corone in plastica (brevettato Scolaro) per aumentare la resistenza e durata, semplificare la manutenzione e migliorare il design.

Con aggancio singolo dedicato per ogni stecca. Tutti gli accessori sono zincati antiruggine e verniciati a polveri colore antracite. Apertura e chiusura con meccanismo a manovella con elegante cornice coprifilo.

Stecca blocco antivento per rendere l'ombrellone più stabile e resistente in caso di vento e con possibilità di inclinazione.

Inclusa base in metallo girevole 360°.

**TESSUTO:** Acrilico Dralon 350gr/m2 impermeabilizzato e trattato antimuffa garantito Teflon. Con camino antivento. Con o senza volant.

#### Strong side post aluminum parasol

**FRAME:** Aluminum and steel structure epoxy coated anthracite color. Side post section 92x92 mm.

Easily interchangeable strong aluminum ribs, section 18x30 (18x35mm size 4x4), with a new plastic crown (patented by Scolaro) in order to increase the resistance and timing, simplify the maintenance and to improve the design.

Ribs are properly fixed to the crown one by one. All components are epoxy coated anthracite color. Easy opening and closing with crank mechanism, whose steel wire is covered by a smart covering.

With wind stop rib for a better stability of the parasol in windy condition and to allow the inclination of the parasol.

360° rotating metallic base is included.

**FABRIC:** Acrylic Dralon 350gr/m2 waterproof Teflon and anti-mold treated. With wind cap. Available with and without valance.



.Dimensione (metri)  
 .Dimensions (meters)  
 .Masse (Meter)  
 .Dimensions (mètrès)  
 .Dimensiones ( en metros)  
 .Afmeting in (meters)



.Stecche  
 .Ribs  
 .Streben  
 .Baleines  
 .Varillas  
 .Baleinen



.Piastre cemento  
 .Cement slabs  
 .Kiesbetonplatten  
 .Dalles ciment  
 .Planchas de cemento  
 .Betontegel



.Viteria in inox e ottone nichelato  
 .Screws in Stainless steel and nickel plated brass  
 .Edelstahlschrauben und vernickeltes Messing  
 .Visserie inox et laiton nickelé  
 .Tornillos en acero inoxidable y bronce niquelado  
 .Schroeven van rvs en vernikkeld messing



.Codice  
 .Code  
 .Artikelcode  
 .Code  
 .Código  
 .Artikelcode



.Set canaline  
 .Raingutter set  
 .Regerinnen  
 .Set gouttières  
 .Canalizador Lluvias  
 .Set regengoten



.Fodero  
 .Cover bag  
 .Schutzhuelle  
 .Housse  
 .Forro  
 .Afdekhoes



.Tipo finitura della struttura/sostegno/componenti  
 .Finishing for frame/structure/components  
 .Ausführung des Gestells/der Struktur/der Bestandteile  
 .Finition armature/structure/composants  
 .Tipo de acabadò de la estructura/Soportes/componente

Pag. 66



.Lunghezza  
 .Length  
 .Laenge  
 .Longueur  
 .Longitud  
 .Lengte



.Con base/supporto  
 .With base/support  
 .Mit Staender/Huelse  
 .Avec base/support  
 .Con base/ soporte  
 .Inclusief standaard




.Doppia carrucola  
 .Double pulley  
 .Doppelter Seilzug  
 .Double poulie  
 .Doble polea  
 .Dubbelle katrollen



.Colore dei componenti/stecche  
 .Component/Ribs colour  
 .Farbe der Bestandteile und Streben  
 .Couleur des composants et baleines  
 .Color de los componentes ò piezas/Varillas ò listones



.Peso  
 .Weight  
 .Gewicht  
 .Poids  
 .Peso  
 .Gewicht



.Sezione stecche  
 .Rib section  
 .Strebenprofil  
 .Section baleines  
 .Sección varillas  
 .Profiel baleinen



.Sistema telescopico  
 .Telescopic system  
 .Teleskopsystem  
 .Système telescopique  
 .Sistema telescópico  
 .Telescoop systeem



.Stecca con sistema "easy change"  
 .Ribs with "easy change" system  
 .Streben mit "easy change" System  
 .Baleines avec "easy change" système  
 .Varillas con sistema de " cambio fácil"  
 .Baleinen met het "easy change" systeem



.Volume (m3)  
 .Volume (m3)  
 .Volumen (m3)  
 .Volume (m3)  
 .Volumen (m3)  
 .Volume (m3)



.Camino antivento  
 .Wind cap  
 .Windfang  
 .Souffle  
 .Chimenea antiviento  
 .Windvang



.Sistema retrattile  
 .Retractile system  
 .Einziehbares System  
 .Système retractile  
 .Sistema retráctil  
 .Inklapbaar systeem



.Ø Palo (mm)  
 .Ø Pole (mm)  
 .Ø Mast (mm)  
 .Ø Mat (mm)  
 .Diametro mm (asta)  
 .Ø Mast (mm)



.Volant  
 .Valance  
 .Volant  
 .Volant  
 .Volant  
 .Faldón  
 .Volant



.Base girevole a 360°C  
 .Revolving base 360°C  
 .360°C drehbarer Staender  
 .Base tournant 360°C  
 .Base giratoria 360°  
 .360° draaibaar



.Massima Stabilità Ottenibile  
 .Maximum Obtainable Stability  
 .Maximal Erhaeltliche Stabilitaet  
 .Maximum De Stabilité Realisable  
 .Maxima Estabilidad Posible  
 .Maximaal Bereikbare Stabiliteit



.Sezione sostegno (mm)  
 .Support section (mm)  
 .Mastprofil (mm)  
 .Section support (mm)  
 .Sección soporte (mm)  
 .Mast (mm)



.Blocco antivento  
 .Wind stop  
 .Windstop  
 .Block antivent  
 .Freno para el viento  
 .Windstop



.Inclinazione fino a 20°  
 .Inclination up to 20°  
 .Neigung bis zu 20°  
 .Inclination jusqu'à 20°  
 .Inclinaciòn hasta 20°



.Peso consigliato in condizioni normali  
 .Recommended weight in normal condition  
 .Empfohlenes gewicht unter normalen bedingungen  
 .Poids recommande dans des conditions normales  
 .Peso recomendado en condiciones normales  
 .Aanbevolen gewicht onder normale omstandigheden



.Ottomatatura  
 .Brassfinishing  
 .Vermessigungen  
 .Laiton doré  
 .Terminaciones doradas  
 .Koper beslag



.Con meccanismo manovella  
 .With winding mechanism  
 .Mit Kurbelmechanismus  
 .Avec mécanisme manivelle  
 .Con manivela  
 .Met opwindmechanisme



.Inclinazione fino a 60°  
 .Inclination up to 60°  
 .Neigung bis zu 60°  
 .Inclination jusqu'à 60°  
 .Inclinaciòn hasta 60°



.Peso minimo richiesto  
 .Minimum ballast required  
 .Erforderliches mindestgewicht  
 .Poids minimum requis  
 .Peso minimo requerido  
 .Minimaal vereist gewicht